

FUEL MANAGEMENT C172 HB-CGF

Total capacity: 68 USG (257 ltr)
Total usable: 62 USG (235 ltr)
Fuel flow: 8.5 USG (32 ltr)/h

US GAL	Liter	lbs	Endurance
1	3.78	6	0h 07
2	7.56	12	0h 14
3	11.34	18	0h 21
4	15.12	24	0h 28
5	18.90	30	0h 35
6	22.68	36	0h 42
7	26.46	42	0h 49
8	30.24	48	0h 56
9	34.02	54	1h 03
10	37.80	60	1h 10
11	41.58	66	1h 17
12	45.36	72	1h 24
13	49.14	78	1h 31
14	52.92	84	1h 38
15	56.70	90	1h 45
16	60.48	96	1h 52
17	64.26	102	1h 59
18	68.04	108	2h 06
19	71.82	114	2h 13
20	75.60	120	2h 20
21	79.38	126	2h 27
22	83.16	132	2h 34
23	86.94	138	2h 41
24	90.72	144	2h 48
25	94.50	150	2h 55
26	98.28	156	3h 02
27	102.06	162	3h 09
28	105.84	168	3h 16
29	109.62	174	3h 23
30	113.40	180	3h 30
31	117.18	186	3h 37
32	120.96	192	3h 44
33	124.74	198	3h 51
34	128.52	204	3h 58

US GAL	Liter	lbs	Endurance
35	132.30	210	4h 05
36	136.08	216	4h 12
37	139.86	222	4h 19
38	143.64	228	4h 26
39	147.42	234	4h 33
40	151.20	240	4h 40
41	154.98	246	4h 47
42	158.76	252	4h 54
43	162.54	258	5h 01
44	166.32	264	5h 08
45	170.10	270	5h 15
46	173.88	276	5h 22
47	177.66	282	5h 29
48	181.44	288	5h 36
49	185.22	294	5h 43
50	189.00	300	5h 50
51	192.78	306	5h 57
52	196.56	312	6h 04
53	200.34	318	6h 11
54	204.12	324	6h 18
55	207.90	330	6h 25
56	211.68	336	6h 32
57	215.46	342	6h 39
58	219.24	348	6h 46
59	223.02	354	6h 53
60	226.80	360	7h 00
61	230.58	366	7h 07
62	234.36	372	7h 14
63	238.14	378	7h 21
64	241.92	384	7h 28
65	245.70	390	7h 35
66	249.48	396	7h 42
67	253.26	402	7h 49
68	257.04	408	7h 56

1 US GAL = 3.78 Liter = 6 lbs