

**FUEL MANAGEMENT C182 HB-CZU**

**Total capacity: 92 USG (348 ltr)**  
**Total usable: 88 USG (333 ltr)**  
**Fuel flow: 13 USG (50 ltr)/h**

US GAL	Liter	lbs	Endurance
1	3.78	6	0h 05
2	7.56	12	0h 09
3	11.34	18	0h 14
4	15.12	24	0h 18
5	18.90	30	0h 23
6	22.68	36	0h 28
7	26.46	42	0h 32
8	30.24	48	0h 37
9	34.02	54	0h 41
10	37.80	60	0h 46
11	41.58	66	0h 51
12	45.36	72	0h 55
13	49.14	78	1h 00
14	52.92	84	1h 05
15	56.70	90	1h 09
16	60.48	96	1h 14
17	64.26	102	1h 18
18	68.04	108	1h 23
19	71.82	114	1h 28
20	75.60	120	1h 32
21	79.38	126	1h 37
22	83.16	132	1h 41
23	86.94	138	1h 46
24	90.72	144	1h 51
25	94.50	150	1h 55
26	98.28	156	2h 00
27	102.06	162	2h 05
28	105.84	168	2h 09
29	109.62	174	2h 14
30	113.40	180	2h 18
31	117.18	186	2h 23
32	120.96	192	2h 28
33	124.74	198	2h 32
34	128.52	204	2h 37
35	132.30	210	2h 41
36	136.08	216	2h 46
37	139.86	222	2h 51
38	143.64	228	2h 55
39	147.42	234	3h 00
40	151.20	240	3h 05
41	154.98	246	3h 09
42	158.76	252	3h 14
43	162.54	258	3h 18
44	166.32	264	3h 23
45	170.10	270	3h 28
46	173.88	276	3h 32

US GAL	Liter	lbs	Endurance
47	177.66	282	3h 37
48	181.44	288	3h 41
49	185.22	294	3h 46
50	189.00	300	3h 51
51	192.78	306	3h 55
52	196.56	312	4h 00
53	200.34	318	4h 05
54	204.12	324	4h 09
55	207.90	330	4h 14
56	211.68	336	4h 18
57	215.46	342	4h 23
58	219.24	348	4h 28
59	223.02	354	4h 32
60	226.80	360	4h 37
61	230.58	366	4h 41
62	234.36	372	4h 46
63	238.14	378	4h 51
64	241.92	384	4h 55
65	245.70	390	5h 00
66	249.48	396	5h 05
67	253.26	402	5h 09
68	257.04	408	5h 14
69	260.82	414	5h 18
70	264.60	420	5h 23
71	268.38	426	5h 28
72	272.16	432	5h 32
73	275.94	438	5h 37
74	279.72	444	5h 41
75	283.50	450	5h 46
76	287.28	456	5h 51
77	291.06	462	5h 55
78	294.84	468	6h 00
79	298.62	474	6h 05
80	302.40	480	6h 09
81	306.18	486	6h 14
82	309.96	492	6h 18
83	313.74	498	6h 23
84	317.52	504	6h 28
85	321.30	510	6h 32
86	325.08	516	6h 37
87	328.86	522	6h 41
88	332.64	528	6h 46
89	336.42	534	6h 51
90	340.20	540	6h 55
91	343.98	546	7h 00
92	347.76	552	7h 05

**1 US GAL = 3.78 Liter = 6 lbs**