

Penn Yan Aero 2 talis Bran Poss Parit Viro, Nove York 1453? HI O 727 7270 / 315 SHS-2000 Final Condition 2018 Www.PsemNar Acrossors

FAA APPROVED SUPPLEMENT

TO THE

PILOT'S OPERATING HANDBOCK AND

FAA APPROVED AIRPLANE FLIGHT MANUAL

FOR

CESSNA MODELS 172N or P

REG. NO. HB-COL

SER. NO. 17274190

This Supplement must be attached to the "Pilot's Operating Handbook and FAA Approved Airplane Flight Manual when the aircraft is modified by the installation of a 180 HP engine and the gross weight is increased in accordance with STC SA703GL. The information contained herein supplements or supersedes the basic manual only in those areas listed. For limitations, procedures and performance information not contained in this Supplement, consult the basic "Pilot's Operating Handbook and FAA Approved Airplane Flight Manual" Flight Manual."

FAA APPROVED:

FOR Chicago Aircraft Certification Office FAA Central Region

DATE: Juna 11, 1985

Page 1 of 4

PENN YAN AERO SERVICE INC

FAA APPROVED
AIRPLANE FLIGHT MANUAL SUPPLEMENT
FOR CESSNA 172 SERIES AIRCRAFT

LOG OF REVIS	SIDNS
--------------	-------

Rev. Page Description FAA Approved Date

No. No. Added performance information to Section 5 for clarification.

Added Log of Revisions Page 2

Renumbered pages Irwin N. Brumer 3/8/94

Page 2 of 4

Penn Yan Aero Service, Inc. 2499 Bath Road, Airport Penn Yan, NY 14527-9599 POH and AFM Supplement for Cessna 172N and P

SECTION ! - General

DESCRIPTIVE DATA

A. Engine

Number of engines: 1 Engine Manufacturer: Avoc Lycoming Engine Model: 0-360-A4A, -A4M, -A4N Horsepower Rating and Speed: 180 rated 8HP at 2700 RPM

8. Propeller

Propeller Manufacturer: Sensenich Propeller Model Number: 76EM8SPY Number of Blades: 2 Propeller Diameter: 76 inches Propeller Type: Fixed Pitch

SECTION II - Limitations

A. The following placard must be displayed in full view of the pilot:

THIS AIRCRAFT HAS BEEN MODIFIED BY THE INSTALLATION OF A 180 HP ENGINE PER STC SA703GL. IT MUST BE OPERATED AS A NORMAL CATEGORY AIRPLANE IN COMPLIANCE WITH THE OPERATING LIMITATIONS AS STATED IN THE FORM OF PLACAROS, MARKINGS AND MANUALS.

8. For the N model aircraft the following placard must be displayed adjacent to the flap position selector switch:

MAXIMUM FLAP TRAVEL IS 30°

C. The following limits apply to the normal category only.

Maximum Gross Weight - 2550 lbs.
C.S. Range - 41.0" to 47.3" at 2550 lbs.
35.0" to 47.3" at 1950 lbs. or less
Straight line variation between points given.

FAA APPROVED JUN 1 1 1985

Page 3 of 4

Section 3

Emergency Procedures

NO CHANGE

Section 4

Normal Procedures

NO CHANGE

Section 5

Performance

Performance of the Cessna 172 series aircraft, when it is modified by the installation of a 180 HP engine and the gross weight is increased, in accordance with STC SA703CL, will be equal to or better than the basic airplane

CAUTION: -

The fuel consumption and range/endurance information originally presented for this model do not apply to this STC modification; increased fuel consumption and reduced range/endurance can be expected with the 180 hp engine installed.

FAA APPROVED DATE: Revised: APR:13 1994

Page 4 Of 4



